



TRACK YOUR TRUCK

GPS FLEET TRACKING

DRIVER PROTECTION

Protect Against:

- Staged Accidents
- False and/or Exaggerated Claims
- Conflicting Reports of Incidents
- Driving allegations (speeding, traffic signal violation, swerving, etc.)

VEHICLE TRACKING

- Real-time GPS Location tagging
- Instant notification of adverse events
- Triggered event reporting

Image Sensor: 2 Megapixel CMOS sensor

Angle of View: 150 °(H : 121.1°, V : 62.4 ± 5%)

Wireless: [CAT1] B2(1900),B4(AWS),B5(850),B12(700AC) B13(700C); [3G] B2(1900),B5(850) (802.11 b/g/n) and Bluetooth (4.2)

Max Data Rate: UL: 5Mbps, DL: 10Mbps

Video Resolution: 1080p(1920x1080) 720p(1280x720) VGA(640x480) 2nd camera: D1(720x480)

Recording Speed: CH1: FHD (30 fps) CH1 + CH2: FHD (15 fps) + D1 (30 fps)

Recording Mode: Continuous, Event and Dual Mode

Memory: Supports SD cards up to 128 GB (FAT32)

GPS / GLONASS: INTERNAL GPS / GLONASS

G-Sensor: Internal 3- axis G-Sensor



DASH HAWK PREMIUM VEHICLE CAMERA

the world's most advanced incident camera with 1080p HD video, built-in WiFi, bluetooth 4.2 and LTE, live GPS position and driver behavior reports to support post incident analysis. The will record exactly what happened before, during and after an incident. It will record the driver's view of the road, vehicle location, impact force, audio, speed, acceleration, braking and steering. We recommended a second camera for recording driver and interior views.



TRACK YOUR TRUCK

GPS FLEET TRACKING

TECHNICAL FEATURES

- 1080P HD video with 150° wide angle lens
- Up to 128 GB SD storage
- Video sent in real-time via email or to your telematics software
- Up to 166 hours of local storage
- Instant notification of events & live GPS location tracking
- Tamper-resistant design
- Built-in WiFi, Bluetooth 4.2 and LTE

Gyro: 3 Axis (X,Y,Z), output rate: 100 Hz

RTC: Internal super capacitors

Speaker: Recording start error

Audio: Internal Microphone

Alarm In / Out: 2 x Alarm In 1x Alarm Out

LED: 3 (Red, Blue, Green LED)

Super Capacitor Enables recording of last file & safe shutdown

Power Input: 12 to 24 Volt DC permanent wiring kit

Input Voltage: DC 5 V, 3 A

Power Consumption: 15 Watt

Delayed Power Shutdown: Supports delayed power shutdown

Size/Weight: 164mm x 640 (w/o brackets) 180g (w/o cable)

Operational Temperature: -10° C ~ 55° C

Storage Temperature: -20°C ~ 85° C

GET IN TOUCH



(815) 717-8482



support@trackyourtruck.com



TrackYourTruck.com

